# Portable
# Fire Extinguishers

## 2.5 GALLON STORED PRESSURE WATER FIRE EXTINGUISHER

## DESCRIPTION

The Buckeye Water Fire Extinguisher provides effective and economical protection for Class A common combustible hazards.

The Water extinguisher uses plain water as its extinguishing agent and can be pressurized with air (or an inert gas such as nitrogen). With a Schrader valve incorporated into the valve assembly, recharging the unit quick, simple, and cost effective.

The extinguisher is manufactured, tested, and Listed to ANSI/UL 626 and ANSI/UL 711 Standards.

Typical Uses: For common combustible fires (fires fueled by wood, paper, cloth, etc.) in offices, classrooms, churches, hotel/motel assembly halls and guest areas.

## SPECIFICATIONS

| | |
|---|---|
| **Model** | 500 |
| **Part Number** | 50000 |
| **UL Rating** | 2A |
| **Capacity** | 2.5 gallons (9.6 liters) |
| **Operating Pressure** | 100 psi (690 kPa) |
| **Discharge time (Seconds)** | 50 |
| **Discharge Range** | 45 – 55 ft. (13.7 – 16.8 m) |
| **Temperature Range** | 40°F to 120°F (4.4°C to 49°C) |
| **USCG Approval** | Type A Size II |
| **Cylinder Construction** | Stainless Steel |
| **Shipping Weight** | 8.3 lbs. (3.7 kg) *Ships empty |
| **Extinguisher Height** | 24.5 in (62.2 cm) |
| **Width w/ Hose Installed** | 9 in (22.9 cm) |
| **Cylinder Diameter** | 7 in (17.8 cm) |
| **Standard Mounting Hardware** | Wall Hook |




110 Kings Road, Kings Mountain, NC 28086-0428
704-739-7415 704-739-7418 www.buckeyef.com